



E-MAXI C

Ausstattung

- Antriebsart: Elektroantrieb
- Schienen-/kabelgebundener Rangierrobot mit gefedertem Treibradsatz
- Moderne Kabine mit vielfältigen Ausstattungsvarianten
- Funkfernsteuerung
- Verschiedene Kuppelsysteme

Technische Daten

- Max. Anhängelast: 1000 t in der Ebene
- Abmessungen: L 6580 x B 2750 x H 4100 mm
- Spurweite: 1435 – 1676 mm, *weitere auf Anfrage*
- Gesamtgewicht: 35 t
- Max. Geschwindigkeit: 2,5 km/h (ohne Last)
- Stufenlos regelbarer Elektroantrieb, 4 Antriebsmotoren mit je 12 kW
- Automatische Auf- / Abwicklung der Kabelzuleitung mithilfe einer Motorleitungstrommel
- Waggonbremsanlage mit Schraubenverdichter (Förderleistung 960 l/min bei 5,1 / 10 bar); optional ALMiG TA11E (Förderleistung 1700 l/min bei 10 bar) wählbar

E-MAXI C

Equipment

- Drive type: Electric drive
- Rail- or cable-guided shunting robot with sprung-suspended driving wheelset
- Modern cab with a wide range of equipment options
- Radio remote control
- Various coupling systems

Technical data

- Max. towing capacity: 1000 t on level ground
- Dimensions: L 6580 x W 2750 x H 4100 mm
- Track gauge: 1435 to 1676 mm, *other gauges on request*
- Total weight: 35 t
- Max. speed: 2.5 km/h (unladen)
- Continuously variable electric drive, 4 drive motors each rated at 12 kW
- Automatic winding and unwinding of the power cable using a motorised cable drum
- Wagon braking system with screw compressor (flow rate 960 l/min at 5.1 / 10 bar); optional ALMiG TA11E (flow rate 1700 l/min at 10 bar) available

GMEINDER LOKOMOTIVEN GmbH

Anton-Gmeinder-Str. 5
74821 Mosbach
Germany
Telefon +49 6261 6747-0
info@gmeinder-lokomotiven.de
www.zagro-group.com

